

A MATLAB LIBRARY OF TEMPORAL DISAGGREGATION METHODS: SUMMARY

Enrique M. Quilis¹

Instituto Nacional de Estadística
Paseo de la Castellana, 183
28046 - Madrid (SPAIN)

December, 2002

¹ The author thanks Ana Abad, Juan Bógalo and Silvia Relloso for their help.

1. INTRODUCTION

The library includes a set of function to perform temporal disaggregation (distribution, averaging and interpolation), according to the following structure:

Adjustment or quadratic programming methods:

- bfl
- denton_uni

served by: tduni_print (ASCII output), tduni_plot (graphic output)

Model-based (or BLUE) methods:

- chowlin
- fernandez
- litterman

served by: td_print (ASCII output), td_plot (graphic output)

Multivariate methods that include a transversal restriction:

- denton
- difonzo

served by: mtd_print (ASCII output), mtd_plot (graphic output)

Extrapolation is feasible using chowlin, fernandez, litterman and difonzo. Constrained extrapolation can be performed also by means of difonzo.

The presentation of the functions is self-contained: help text, script to run the function and output (ASCII file and plots).

Matlab source code is freely available if requested at: info@ine.es

2. BOOT-FEIBES-LISMAN

PURPOSE: Temporal disaggregation using the Boot-Feibes-Lisman method

SYNTAX: res=bfl(Y,ta,d,s);

OUTPUT: res: a structure
res.meth = 'Boot-Feibes-Lisman';
res.N = Number of low frequency data
res.ta = Type of disaggregation
res.s = Frequency conversion
res.d = Degree of differencing
res.y = High frequency estimate
res.et = Elapsed time

INPUT: Y: Nx1 ---> vector of low frequency data
ta: type of disaggregation
ta=1 ---> sum (flow)
ta=2 ---> average (index)
ta=3 ---> last element (stock) ---> interpolation
d: objective function to be minimized: volatility of ...
d=0 ---> levels
d=1 ---> first differences
d=2 ---> second differences
s: number of high frequency data points for each low frequency data point
s= 4 ---> annual to quarterly
s=12 ---> annual to monthly
s= 3 ---> quarterly to monthly

LIBRARY: aggreg

SEE ALSO: tduni_print, tduni_plot

REFERENCE: Boot, J.C.G., Feibes, W. y Lisman, J.H.C. (1967)
"Further methods of derivation of quarterly figures from annual data",
Applied Statistics, vol. 16, n. 1, p. 65-75.

Application:

```
Y=load('c:\x\td\data\Y.anu');  
res=bfl(Y,1,1,12);  
tduni_print(res,'td.sal');  
tduni_plot(res);  
edit td.sal
```

ASCII file containing detailed output:

```
*****  
TEMPORAL DISAGGREGATION METHOD: Boot-Feibes-Lisman  
*****
```


```
-----  
Number of low-frequency observations : 22  
Frequency conversion : 12  
Number of high-frequency observations : 264  
-----
```

```
Degree of differencing : 1  
Type of disaggregation: sum (flow).  
-----
```

```
High frequency series (columnwise):  
-----
```

```
4972.2800  
4971.1389  
.....  
.....  
.....  
7898.7692  
7899.3631  
7899.6600  
-----
```

```
Elapsed time: 0.3200  
-----
```



3. DENTON

PURPOSE: Temporal disaggregation using the Denton method

SYNTAX: res=denton_uni(Y,x,ta,d,s);

OUTPUT: res: a structure
res.meth = 'Denton';
res.N = Number of low frequency data
res.ta = Type of disaggregation
res.s = Frequency conversion
res.d = Degree of differencing
res.y = High frequency estimate
res.U = Low frequency residuals
res.u = High frequency residuals
res.et = Elapsed time

INPUT: Y: Nx1 ---> vector of low frequency data
x: nx1 ---> vector of low frequency data
ta: type of disaggregation
ta=1 ---> sum (flow)
ta=2 ---> average (index)
ta=3 ---> last element (stock) ---> interpolation
d: objective function to be minimized: volatility of ...
d=0 ---> levels
d=1 ---> first differences
d=2 ---> second differences
s: number of high frequency data points for each low frequency data point
s= 4 ---> annual to quarterly
s=12 ---> annual to monthly
s= 3 ---> quarterly to monthly

LIBRARY: aggreg, bfl

SEE ALSO: tduni_plot, tduni_print


REFERENCE: Denton, F.T. (1971) "Adjustment of monthly or quarterly series to annual totals: an approach based on quadratic minimization", Journal of the American Statistical Society, vol. 66, n. 333, p. 99-102.

Application:

```
Y=load('c:\x\td\data\Y.prn');  
x=load('c:\x\td\data\x.ind');  
res=denton_uni(Y,x,1,1,4);  
tduni_print(res,'td.sal');  
tduni_plot(res);  
edit td.sal
```

ASCII file containing detailed output:

```
*****
TEMPORAL DISAGGREGATION METHOD: Denton
*****
-----
Number of low-frequency observations : 22
Frequency conversion                 : 4
Number of high-frequency observations : 88
-----
Degree of differencing               : 1
Type of disaggregation: sum (flow).
-----
High frequency series (columnwise):
-----
15374.9285
15169.7571
.....
.....
.....
24883.3098
20609.0705
24415.4509
-----
Elapsed time: 0.0500
-----
```



4. CHOW-LIN

PURPOSE: Temporal disaggregation using the Chow-Lin method

SYNTAX: res=chowlin(Y,x,ta,s,type);

OUTPUT: res: a structure

res.meth = 'Chow-Lin';
res.ta = type of disaggregation
res.type = method of estimation
res.N = nobs. of low frequency data
res.n = nobs. of high-frequency data
res.pred = number of extrapolations
res.s = frequency conversion between low and high freq.
res.p = number of regressors (including intercept)
res.Y = low frequency data
res.x = high frequency indicators
res.y = high frequency estimate
res.y_dt = high frequency estimate: standard deviation
res.y_lo = high frequency estimate: sd - sigma
res.y_up = high frequency estimate: sd + sigma
res.u = high frequency residuals
res.U = low frequency residuals
res.beta = estimated model parameters
res.beta_sd = estimated model parameters: standard deviation
res.beta_t = estimated model parameters: t ratios
res.rho = innovational parameter
res.aic = Information criterion: AIC
res.bic = Information criterion: BIC
res.val = Objective function used by the estimation method
res.r = grid of innovational parameters used by the estimation method

INPUT: Y: Nx1 ---> vector of low frequency data

x: nxp ---> matrix of high frequency indicators (without intercept)

ta: type of disaggregation

ta=1 ---> sum (flow)

ta=2 ---> average (index)

ta=3 ---> last element (stock) ---> interpolation

s: number of high frequency data points for each low frequency data points

s= 4 ---> annual to quarterly

s=12 ---> annual to monthly

s= 3 ---> quarterly to monthly

type: estimation method:

type=0 ---> weighted least squares

type=1 ---> maximum likelihood

LIBRARY: aggreg

SEE ALSO: litterman, fernandez, td_plot, td_print

REFERENCE: Chow, G. y Lin, A.L. (1971) "Best linear unbiased distribution and extrapolation of economic time series by related series", Review of Economic and Statistics, vol. 53, n. 4, p. 372-375.

Application:

```
Y=load('c:\x\td\data\Y.prn');
x=load('c:\x\td\data\x.ind');
res=chowlin(Y,x,1,4,1);
td_print(res,'td.sal',1); % op1=1: series are printed in ASCII file
td_plot(res);
edit td.sal
```

ASCII file containing detailed output:

```
*****
TEMPORAL DISAGGREGATION METHOD: Chow-Lin
*****
-----
Number of low-frequency observations : 22
Frequency conversion : 4
Number of high-frequency observations: 88
Number of extrapolations : 0
Number of indicators (+ constant) : 2
-----
Type of disaggregation: sum (flow).
-----
Estimation method: Maximum likelihood.
-----
Beta parameters (columnwise):
* Estimate
* Std. deviation
* t-ratios
-----
215.4518      111.7079      1.9287
 0.9828      0.0069      142.0272
-----
Innovational parameter: 0.7600
-----
AIC: 10.0340
BIC: 10.1828
-----
Low-frequency correlation
- levels : 0.9998
- yoy rates : 0.9617
-----
High-frequency correlation
- levels : 0.9998
- yoy rates : 0.9812
-----
High-frequency volatility of yoy rates
- estimate : 8.4282
- indicator : 9.0226
- ratio : 0.9341
-----
```

High frequency series (columnwise):





- * Estimate
- * Std. deviation
- * 1 sigma lower limit
- * 1 sigma upper limit
- * Residuals





```

-----
5400.9896      114.8247      5286.1649      5515.8143      112.3095
5311.2409      83.7296       5227.5112      5394.9705      128.7034
.....
.....
.....
30079.6885     86.7557       29992.9328     30166.4443     -97.4913
25874.7702     86.2867       25788.4835     25961.0569     -43.9249
29614.4998     116.3242      29498.1756     29730.8240     -16.2417
-----

```

Elapsed time: 1.8100





A variant to be applied with a fixed innovational parameter:

PURPOSE: Temporal disaggregation using the Chow-Lin method
rho parameter is fixed (supplied by the user)

SYNTAX: res=chowlin_fix(Y,x,ta,s,type,rho);

5. FERNÁNDEZ

PURPOSE: Temporal disaggregation using the Fernandez method

SYNTAX: res=fernandez(Y,x,ta,s);

OUTPUT: res: a structure

res.meth = 'Fernandez';
res.ta = type of disaggregation
res.type = method of estimation
res.N = nobs. of low frequency data
res.n = nobs. of high-frequency data
res.pred = number of extrapolations
res.s = frequency conversion between low and high freq.
res.p = number of regressors (including intercept)
res.Y = low frequency data
res.x = high frequency indicators
res.y = high frequency estimate
res.y_dt = high frequency estimate: standard deviation
res.y_lo = high frequency estimate: sd - sigma
res.y_up = high frequency estimate: sd + sigma
res.u = high frequency residuals
res.U = low frequency residuals
res.beta = estimated model parameters
res.beta_sd = estimated model parameters: standard deviation
res.beta_t = estimated model parameters: t ratios
res.aic = Information criterion: AIC
res.bic = Information criterion: BIC

INPUT: Y: Nx1 ---> vector of low frequency data

x: nxp ---> matrix of high frequency indicators (without intercept)

ta: type of disaggregation

ta=1 ---> sum (flow)

ta=2 ---> average (index)

ta=3 ---> last element (stock) ---> interpolation

s: number of high frequency data points for each low frequency data points

s= 4 ---> annual to quarterly

s=12 ---> annual to monthly

s= 3 ---> quarterly to monthly

LIBRARY: aggreg

SEE ALSO: chowlin, litterman, td_plot, td_print

REFERENCE: Fernández, R.B.(1981)"Methodological note on the estimation of time series", Review of Economic and Statistics, vol. 63, n. 3, p. 471-478.

Application:

```

Y=load('c:\x\td\data\Y.prn');
x=load('c:\x\td\data\x.tri');
res=fernandez(Y,x,1,4);
td_print(res,'td.sal',1); % op1=1: series are printed in ASCII file
td_plot(res);
edit td.sal

```

ASCII file containing detailed output:

```

*****
TEMPORAL DISAGGREGATION METHOD: Fernandez
*****
-----
Number of low-frequency observations : 22
Frequency conversion : 4
Number of high-frequency observations: 90
Number of extrapolations : 2
Number of indicators (+ constant) : 2
-----
Type of disaggregation: sum (flow).
-----
Estimation method: Maximum likelihood.
-----
Beta parameters (columnwise):
* Estimate
* Std. deviation
* t-ratios
-----
564.9834      195.9404      2.8834
  0.9360      0.0292      32.0284
-----
Innovational parameter: 1.0000
-----
AIC: 9.6079
BIC: 9.7567
-----
Low-frequency correlation
- levels : 0.9998
- yoy rates : 0.9617
-----
High-frequency correlation
- levels : 0.9997
- yoy rates : 0.9817
-----
High-frequency volatility of yoy rates
- estimate : 8.3477
- indicator : 9.1506
- ratio : 0.9123
-----

```

High frequency series (columnwise):

- * Estimate
- * Std. deviation
- * 1 sigma lower limit
- * 1 sigma upper limit
- * Residuals

5396.6742	91.6250	5305.0492	5488.2992	-0.0000
5297.9198	60.8871	5237.0327	5358.8069	2.3349
.....
.....
.....
30021.1833	73.6977	29947.4856	30094.8810	920.9566
26022.3844	108.3992	25913.9852	26130.7837	977.8951
29586.1687	92.9937	29493.1750	29679.1625	1006.3644
.....
28366.5459	140.8431	28225.7028	28507.3889	1006.3644
29461.6792	176.5235	29285.1557	29638.2027	1006.3644

Elapsed time: 0.0500

Graphs are the same than in the Chow-Lin case, except that the first one (objective function vs innovational parameter) is not generated.

6. LITTERMAN

PURPOSE: Temporal disaggregation using the Litterman method

SYNTAX: res=litterman(Y,x,ta,s,type);

OUTPUT: res: a structure

res.meth = 'Litterman';
res.ta = type of disaggregation
res.type = method of estimation
res.N = nobs. of low frequency data
res.n = nobs. of high-frequency data
res.pred = number of extrapolations
res.s = frequency conversion between low and high freq.
res.p = number of regressors (including intercept)
res.Y = low frequency data
res.x = high frequency indicators
res.y = high frequency estimate
res.y_dt = high frequency estimate: standard deviation
res.y_lo = high frequency estimate: sd - sigma
res.y_up = high frequency estimate: sd + sigma
res.u = high frequency residuals
res.U = low frequency residuals
res.beta = estimated model parameters
res.beta_sd = estimated model parameters: standard deviation
res.beta_t = estimated model parameters: t ratios
res.rho = innovational parameter
res.aic = Information criterion: AIC
res.bic = Information criterion: BIC
res.val = Objective function used by the estimation method
res.r = grid of innovational parameters used by the estimation method

INPUT: Y: Nx1 ---> vector of low frequency data

x: nxp ---> matrix of high frequency indicators (without intercept)

ta: type of disaggregation

ta=1 ---> sum (flow)

ta=2 ---> average (index)

ta=3 ---> last element (stock) ---> interpolation

s: number of high frequency data points for each low frequency data points

s= 4 ---> annual to quarterly

s=12 ---> annual to monthly

s= 3 ---> quarterly to monthly

type: estimation method:

type=0 ---> weighted least squares

type=1 ---> maximum likelihood

LIBRARY: aggreg

SEE ALSO: chowlin, fernandez, td_plot, td_print

REFERENCE: Litterman, R.B. (1983a) "A random walk, Markov model for the distribution of time series", Journal of Business and Economic Statistics, vol. 1, n. 2, p. 169-173.

Application:

```
Y=load('c:\x\td\data\Y.prn');
x=load('c:\x\td\data\x.tri');
res=litterman(Y,x,1,4,0);
td_print(res,'td.sal',0); % op1=0: series are not printed in ASCII file
td_plot(res);
edit td.sal
```

ASCII file containing detailed output:

```
*****
TEMPORAL DISAGGREGATION METHOD: Litterman
*****
-----
Number of low-frequency observations : 22
Frequency conversion : 4
Number of high-frequency observations: 90
Number of extrapolations : 2
Number of indicators (+ constant) : 2
-----
Type of disaggregation: sum (flow).
-----
Estimation method: Weighted least squares.
-----
Beta parameters (columnwise):
* Estimate
* Std. deviation
* t-ratios
-----
1205.4851      233.5241      5.1621
   0.7910      0.0480      16.4821
-----
Innovational parameter: 0.9700
-----
AIC: 7.9478
BIC: 8.0966
-----
Low-frequency correlation
- levels : 0.9998
- yoy rates : 0.9617
-----
High-frequency correlation
- levels : 0.9994
- yoy rates : 0.9735
-----
High-frequency volatility of yoy rates
- estimate : 7.6249
- indicator : 9.1506
- ratio : 0.8333
-----
Elapsed time: 2.5300
-----
```

A variant to be applied with a fixed innovational parameter:

PURPOSE: Temporal disaggregation using the Litterman method
mu parameter is fixed (supplied by the user)

SYNTAX: res=litterman(Y,x,ta,s,type,mu);

Graphical output contains the same information than in the Chow-Lin case.

7. MULTIVARIATE DENTON

PURPOSE: Multivariate temporal disaggregation with transversal constraint

SYNTAX: res = denton(Y,x,z,ta,s,d);

OUTPUT: res: a structure
res.meth = 'Multivariate Denton';
res.N = Number of low frequency data
res.n = Number of high frequency data
res.pred = Number of extrapolations (=0 in this case)
res.ta = Type of disaggregation
res.s = Frequency conversion
res.d = Degree of differencing
res.y = High frequency estimate
res.et = Elapsed time

INPUT: Y: NxM ---> M series of low frequency data with N observations
x: nxM ---> M series of high frequency data with n observations
z: nx1 ---> high frequency transversal constraint
ta: type of disaggregation
ta=1 ---> sum (flow)
ta=2 ---> average (index)
ta=3 ---> last element (stock) ---> interpolation
s: number of high frequency data points for each low frequency data points
s= 4 ---> annual to quarterly
s=12 ---> annual to monthly
s= 3 ---> quarterly to monthly
d: objective function to be minimized: volatility of ...
d=0 ---> levels
d=1 ---> first differences
d=2 ---> second differences

LIBRARY: aggreg, dif, vec, desvec

SEE ALSO: difonzo, mtd_print, mtd_plot



REFERENCE: di Fonzo, T. (1994) "Temporal disaggregation of a system of time series when the aggregate is known: optimal vs. adjustment methods", INSEE-Eurostat Workshop on Quarterly National Accounts, Paris, december



Application:

```
Y=load('YY.anu'); % Loading low frequency data
x=load('x.tri'); % Loading high frequency data
z=load('z.prn'); % Loading high frequency transversal restriction
res=denton(Y,x,z,2,4,1);
mtd_print(res,'mtd.sal');
edit mtd.sal;
mtd_plot(res,z);
```

ASCII file containing detailed output:

```
*****
TEMPORAL DISAGGREGATION METHOD: Multivariate Denton
*****
-----
Number of low-frequency observations : 23
Frequency conversion                 : 4
Number of high-frequency observations : 92
Number of extrapolations             : 0
-----
Degree of differencing               : 1
Type of disaggregation: average (index).
-----
High frequency series (columnwise):
* Point estimate
-----
3752.9096  4982.6505
3459.3681  5257.1693
.....
.....
.....
2757.8458  8545.8074
2825.1411  8624.4561
2867.5816  8657.9733
-----
Elapsed time: 0.2800
```





8. DI FONZO

PURPOSE: Multivariate temporal disaggregation with transversal constraint

SYNTAX: res = difonzo(Y,x,z,ta,s,type);

OUTPUT: res: a structure

res.meth = 'Multivariate di Fonzo';
res.N = Number of low frequency data
res.n = Number of high frequency data
res.pred = Number of extrapolations
res.ta = Type of disaggregation
res.s = Frequency conversion
res.type = Model for high frequency innovations
res.beta = Model parameters
res.y = High frequency estimate
res.d_y = High frequency estimate: std. deviation
res.et = Elapsed time

INPUT: Y: NxM ---> M series of low frequency data with N observations

x: nxM ---> M series of high frequency data with n observations

z: nx1 ---> high frequency transversal constraint with nz obs.

ta: type of disaggregation

ta=1 ---> sum (flow)

ta=2 ---> average (index)

ta=3 ---> last element (stock) ---> interpolation

s: number of high frequency data points for each low frequency data points

s= 4 ---> annual to quarterly

s=12 ---> annual to monthly

s= 3 ---> quarterly to monthly

type: model for the high frequency innovations

type=0 ---> multivariate white noise

type=1 ---> multivariate random walk

NOTE: Extrapolation is automatically performed when $n > sN$.

If $n = nz > sN$ restricted extrapolation is applied.

Finally, if $n > nz > sN$ extrapolation is performed in constrained

form in the first $nz - sN$ observations and in free form in

the last $n - nz$ observations.

LIBRARY: aggreg, dif, vec, desvec

SEE ALSO: denton, mtd_print, mtd_plot

REFERENCE: di Fonzo, T.(1990)"The estimation of M disaggregate time series when contemporaneous and temporal aggregates are known", Review of Economics and Statistics, vol. 72, n. 1, p. 178-182.

Application:

```
Y=load('YY.anu'); % Loading low frequency data
x=load('x.tri'); % Loading high frequency data
z=load('z.prn'); % Loading high frequency transversal restriction
res = difonzo(Y,x,z,2,4,1);
mtd_print(res,'mtd.sal');
edit mtd.sal;
mtd_plot(res,z);
```

ASCII file containing detailed output:

```
*****
TEMPORAL DISAGGREGATION METHOD: Multivariate di Fonzo
*****
-----
Number of low-frequency observations : 23
Frequency conversion                 : 4
Number of high-frequency observations : 92
Number of extrapolations             : 0
-----
Model for the innovations: random walk.
Type of disaggregation: average (index).
-----
High frequency series (columnwise):
* Point estimate
-----
3413.3839  5322.1762
3447.4092  5269.1282
.....
.....
.....
2758.4657  8545.1875
2817.9882  8631.6090
2856.1605  8669.3944
```

High frequency series (columnwise):
* Std. desviation

197.8732 197.8732
127.3900 127.3900
.....
.....
.....
137.9397 137.9397
128.1006 128.1006
194.9112 194.9112

Elapsed time: 0.3300

